



Comline CO 5W30

5W-30

Fully synthetic motor oil for petrol and diesel engines, with or without turbo

Description:

Comline CO 5W30 is a fully synthetic motor oil for petrol and diesel engines in passenger cars and light duty commercial vehicles. This oil can be applied for cars equipped with catalytic converters, turbo charged engines and for direct fuel injection systems.

Comline CO 5W30 provides an extremely quick and stable lubricant film during the cold start-up and offers high thermal stability under heavy duty operating conditions.

Comline CO 5W30 not only offers extremely good wear protection, but also protects against rust and corrosion, while special additives keep all parts free from dirt, sludge and deposits.

Comline CO 5W30 offers fuel saving properties and can be mixed with both synthetic and mineral motor oils.

Performance level:

5W-30:
API SM/CF
ACEA A3/B4 (07)
MB 229.3
VW 502.00/505.00
BMW LL-98

Typical values

5W-30

Density 20°C	Kg/L	0.851
Viscosity 100°C	cSt	11.0
Viscosity 40°C	cSt	65.0
Viscosity -30°C	cP	<6600
Viscosity -35°C	cP	-
Viscosity Index		162
Flash point COC	°C	>210
Pour point	°C	<-36
Sulphated ash	Wt%	1.2

THIS SHEET CONTAINS RECOMMENDATIONS OR SUGGESTIONS ON PROPERTIES AND POSSIBLE APPLICATIONS OF COMLINE PRODUCTS. BECAUSE OF CONTINUOUS PRODUCT RESEARCH AND DEVELOPMENT, THE INFORMATION IN THIS DOCUMENT CAN BE CHANGED AT ALL TIMES, WITHOUT FOREGOING NOTICE. THE ANALYTICAL INFORMATION IN THIS DOCUMENT CONSISTS OF TYPICAL VALUES. ALTHOUGH THE TEXT HAS BEEN REDACTED WITH GREAT CAREFULNESS, THE AUTHOR WILL NOT ACCEPT ANY LIABILITY FOR DAMAGES CAUSED BY INCOMPLETENESS AND/OR INCORRECTNESS OF THE TEXT. THE READER IS ADVISED TO MAKE THE FINAL PRODUCT CHOICE IN DIALOGUE WITH THE SUPPLIER.