

Product Specification

CO10W-30STOU

Heavy Duty Mineral Engine Oil

1 L	4 L	5 L	20 L	60 L	200L
CO10W30STOU-1	CO10W30STOU-4	CO10W30STOU-5	CO10W30STOU-20	CO10W30STOU-60	CO10W30STOU-200

LEVELS OF QUALITY

The lubricant CO10W-30STOU complies with the following international specifications:

ACEA E3; API CG-4/SF; CNH MAT 3525, 3526; FORD M2C 159B, 159C, 134D; JD J27, J20C, J20D; MB 228.1; MF CMD M1135, M1139, M1143, M1144, M1145; NH 82009201, 02, 03; ZF TE-ML 06A, 06B, 07B

DESCRIPTION

A multigrade and multifunctional oil of STOU type, especially recommended for all types of agricultural diesel engines. The quality of basic oils along with a reliable additive package guarantee an efficient engine cleaning and protection of mechanical components against wear, even under heavy operating conditions, by providing the lubricant with:

- An excellent anti-wear capability,
- Detergent and dispersant power,
- An excellent fluidity at low temperature
- An excellent oxidation resistance.

APPLICATIONS

CO10W-30 S.T.O.U. is a multifunctional product to be used in all agriculture and earthmoving systems, whenever a product complying with newer versions of the specification is required. The following benefits can be obtained if you use this product:

- A higher engine cleaning,
- A better protection and longer engine life,
- A good cold start.

SAE Scale		10W/30
Density at 15°C.Kg./dm3	ASTM D1298	0.870
Viscosity at 100°C.cSt	ASTM D445	11.5
Viscosity Index	ASTM D2270	135
Flammability V.A.°C	ASTM D92	205
Pour Point °C	ASTM D97	-27
T.B.N.	ASTM D2896	9

The above-mentioned values are indicative of production average values and are not an integral part of the specification.

TDS Comline 10W-30STOU_REV.2 October 2021