



## Product Specification

Edition: 26/02/2015

### COATF1100

Automatic transmission fluid

Substit.  
edition:

**MEETS SPECS:** AISIN WARNER JWS 3309 ATs-AW-1, JASO M315 Type 1A, Chrysler MOPAR ATF+3/+4, Toyota Type T, T-II, T-III, T-IV, Type D-2, Type WS, Nissan MaticFluid C/D/J/K/S, Mitsubishi/Hyundai/Kia SP-II/SP-III/SP-IV, Subaru PN K0710Y0700, Isuzu BESCO ATF-II/ATF-III, Suzuki ATF Oil/ATF Oil Special/JWS 3314, Mazda ATF M-V, Daihatsu Alumix ATF Multi, Honda ATF Z1 (exceptCVT), GM Daewoo & GM US 88900925 (T-IV), VW G 055 005, VW G 055 025 / VW 052 162, AUDI G052 025A2, FORD M2C-166H - MERCON FORD M2C-202B - MERCON V-MERCON SP/LV - FORD M2C-919E, DEXRON IID/E IIIG IIIH ZF TE-ML 03D/04D/09B/14A/14B /16L/17C, ZF COMMERCIAL ATS, BMW 4-5 SPEED, VOITH ATS 55.6335, MAN 339TYPE Z1/Z2/Z3-V1/V2 MB 236.9-236.10, VOLVO 1161540 -8

PARAMETERS	MEASURE UNIT	METHOD	VALUE		
			MIN.	MAX	TYP.
Appearance		ASTM D 4176/1	C & B		
Specific gravity at 15°C	Kg/mc	ASTM D 1298		860	
Viscosity at 40°C	cSt	ASTM D 445			33
Viscosity at 100°C	cSt	ASTM D 445	6,8	8,0	
Viscosity index		ASTM D 2270	160		
Flash point COC	°C	ASTM D 92	180		
Pour point	°C	ASTM D 97		-33	