



## Product Specification

### CO5W-20ECO Fully-Synthetic EcoBoost Engine Oil

1 L	4 L	5 L	20 L	60 L	200L
CO5W20ECO-1	CO5W20ECO-4	CO5W20ECO-5	CO5W20ECO-20	CO5W20ECO-60	CO5W20ECO-200

#### LEVELS OF QUALITY

The lubricant CO5W-20ECO complies with the following international specifications:

API SN, ILSAC GF-5, ACEA C2, A1/B1, FORD WSS-M2C948-B/A, FIAT 9.55535-CR1, BMW LL-14 FE+, JLR STJLR 51.5122-STJLR 03.5004

#### DESCRIPTION

CO5W-20ECO is a Synthetic high-performance high-lubricity engine oil specially developed for Ford EcoBoost® series engines. The latest base fluids in combination with special additives guarantee very rapid distribution of the oil and optimized frictional properties. Unique lubricity characteristics cut fuel consumption and thus reduce emissions of pollutants.

Due to its characteristics CO5W-20ECO is predominantly used in Euro 5/6 engines where an ACEA A1/B1 engine oil is specified. As CO5W-20ECO will be our basis for new engine designs good biofuel compatibility is provided.

SAE Scale		5W-20
Density at 15°C.Kg./dm <sup>3</sup>	ASTM D1298	0.836
Viscosity at 100°C.cSt	ASTM D445	8.5
Viscosity Index	ASTM D2270	155
Flammability V.A.°C	ASTM D92	200
Pour Point °C	ASTM D97	-39
S.A.	ASTM D874	0.78
T.B.N.	ASTM D2896	8.2

The above mentioned values are indicative of production average values and are not an integral part of the specification.

**TDS Comline 5W-20ECO\_REV.2 March 2020**

Comline Auto Parts Ltd

Unit B1 Luton Enterprise Park, Sundon Park Road, Luton, Bedfordshire, LU3 3GU, Great Britain

T: +44 1582 578 888 | F: +44 1582 578 889