



## Product Specification

### CO5W-40PD Fully-Synthetic Engine Oil

1 L	4 L	5 L	20 L	60 L	200L
CO5W40PD-1	CO5W40PD-4	CO5W40PD-5	CO5W40PD-20	CO5W40PD-60	CO5W40PD-200

#### LEVELS OF QUALITY

The lubricant CO5W-40PD complies with the following international specifications:

API SN SM/CF, ACEA C3, MB 229.51-229.31, MB 226.5, BMW LONG LIFE 04, FORD WSS-M2C917A, VW 502.00-505.00-505.01, PORSCHE C40, GM DEXOS 02, FIAT 9.55535.S2/GH2, RENAULT RN0700-RN0710, PSA B71 2297

#### DESCRIPTION

CO5W-40PD is a 100% synthetic lubricant with low ash content (MID SAPS) produced at the highest formulation levels, designed to provide excellent performances in modern turbocharged petrol and diesel engines complying with the new EURO IV and EURO V emission regulations. The modern formulation technology with low ash content allows the extension of life and maintaining the efficiency of emission reduction systems of petrol and diesel cars (DPF, TWC, FAP) unchanged.

Furthermore CO5W-40PD has been specifically designed to satisfy the latest ACEA C3 specifications with a mid ash content and is recommended for engines equipped with particulate filtration systems, maintenance-free and without fuel additives.

SAE Scale		5W-40
Density at 15°C.Kg./dm <sup>3</sup>	ASTM D1298	0.850
Viscosity at 100°C.cSt	ASTM D445	13.2
Viscosity Index	ASTM D2270	155
Flammability V.A.°C	ASTM D92	218
Pour Point °C	ASTM D97	-36
S.A.	ASTM D874	0.75
T.B.N.	ASTM D2896	7.4

The above mentioned values are indicative of production average values and are not an integral part of the specification.

**TDS Comline 5W-40PD\_REV.4 March 2020**

Comline Auto Parts Ltd

Unit B1 Luton Enterprise Park, Sundon Park Road, Luton, Bedfordshire, LU3 3GU, Great Britain

T: +44 1582 578 888 | F: +44 1582 578 889